DRAFT HYDROGEOLOGIC CONCEPTUAL SITE MODEL REPORT

Former Payless/Allstate, Avis and National Facilities McCarran International Airport Las Vegas, Nevada

Prepared For:
OGI Environmental LLC
Broadbent & Associates, Inc.
Converse Consultants

Prepared By: Geo Blue Consulting, Inc. 78 Throckmorton Ave., Suite 3 Mill Valley, California 94941

28 August 2018

TABLE OF CONTENTS

		Page
1.0	INTRODUCTION	1
1.1	Objective	
1.2	HYDROGEOLOGIC CSM DEVELOPMENT	
2.0	SITE DESCRIPTION	
2.1	LOCATION	
2.2	CLIMATECURRENT AND FUTURE LAND USE	
3.0	HISTORICAL SITE INFORMATION	
4.0	REGIONAL GEOLOGIC SETTING	
4.1	GEOMETRY OF THE ALLUVIAL GROUNDWATER BASIN	
4.2 4.3	COMPOSITION OF ALLUVIUM AND PLAYA DEPOSITS	
5.0	REGIONAL GROUNDWATER CONDITIONS	
5.1	Occurrence and Depths	
5.1	GROUNDWATER FLOW DIRECTIONS AND GRADIENTS	
5.3	LVVWD HYDROSTRATIGRAPHIC UNITS IN THE MWFA	7
5.4	BASIN-WIDE HYDROGEOLOGIC FRAMEWORK	
5.5 5.6	SHALLOW GROUNDWATER SEPARATION FROM DEEPER AQUIFERS	
5.7	REGIONAL WATER QUALITY	
6.0	SURFACE WATER BODIES	9
7.0	NEARBY WATER WELLS	9
8.0	SITE GEOLOGY	10
8.1	Surface Geology	10
8.2	LITHOLOGY OF LOGGED SEDIMENTS	
8.3 8.4	DEEPER SITE GEOLOGY	
	Interpretive Geologic Cross Sections/est of Paradise Road	
	etween Paradise Road and Swenson Street	
	etween Swenson and Wilbur Streets	
	etween Wilbur Street and Maryland Parkway	
9.0	SITE HYDROGEOLOGY	13
9.1	DEPTH TO GROUNDWATER	
D	ecreasing Depth Toward Maryland Parkway	13

9.2	GROUNDWATER FLOW DIRECTIONS AND GRADIENT	14
9.3	AMBIENT WATER QUALITY	
9.4	HYDROSTRATIGRAPHY	
10.0	PREFERENTIAL PATHWAYS	15
11.0	RELEASE SOURCE/UST SYSTEMS	16
12.0	LNAPL	17
13.0	CONTAMINANTS OF CONCERN	17
14.0	SOIL IMPACTS	17
15.0	SOIL GAS IMPACTS	18
16.0	GROUNDWATER IMPACTS	18
16.1	Source Areas at the Facilities	19
16.2	DOWNGRADIENT AREAS	19
17.0	REFERENCES	20

FIGURES

Figure 1 - Site Area
Figure 2 - Site Vicinity
Figure 3 - Current Site Uses - McCarran Economy Parking

Figure 4 - Las Vegas Valley Physiographic Features and Groundwater Flow Directions

(Liesing, 2004)

Figure 5 - Las Vegas Valley Hydrostratigraphic Units

Figure 6 - Surface Geology in the Site Vicinity

Figure 7 - Change in Potentiometric Surface of the Producing Aquifers, 1990 to 1999 (Liesing, 2004)

Figure 8 - Idealized Basin Flow (Domenico, 1964)

Figure 9 - Fence Diagram Showing Lithology and Water-Bearing Properties (Plume, 1989)

Figure 10 - Surface Water Bodies - Unnamed Wash
Figure 11 - Sensitive Receptor Survey (Broadbent, 2016)

APPENDICES

Appendix A Interpretive Cross-Sections

Appendix B Presentation slides from the 9 May 2013 and 4 February 2014 meetings

Appendix C Groundwater Elevation Contours and Plotted MTBE and TBA Concentrations in Monitoring Wells



HYROGEOLOGIC CONCEPTUAL SITE MODEL REPORT

McCarran International Airport
Las Vegas, Nevada
Former Payless/Allstate and National Facilities

1.0 INTRODUCTION

Geo Blue Consulting, Inc. (Geo Blue) prepared this report describing the hydrogeologic portion of the Conceptual Site Model (CSM) common to the Payless/Allstate (8-00006), Avis (8-000217), and National (8-000416) facilities, formerly located at McCarran International Airport (McCarran Airport) on Rent-A-Car Road in Las Vegas, Nevada. The Nevada Division of Environmental Protection (NDEP) is directing cleanup of gasoline releases, including methyl tert-butyl ether (MTBE) and tert-butyl alcohol (TBA) in groundwater beneath and downgradient of the facilities. The downgradient MTBE and TBA plumes are regulated by the NDEP as a commingled plume. The NDEP required that the responsible parties for these three facilities prepare this report to summarize background information for the investigation and remediation of the former car rental facilities. Geo Blue prepared this report at the request of the Certified Environmental Managers (CEMs) for the responsible parties, including OGI Environmental LLC (OGI), Broadbent & Associates, Inc. (Broadbent), and Converse Consultants (Converse).

1.1 OBJECTIVE

This hydrogeologic portion of the CSM describes the geologic framework and groundwater conditions which are common to the former Payless, Avis, and National car rental facilities. The interpreted hydrogeology includes description of hydrostratigraphy, groundwater flow direction evaluation, and identification of potential MTBE and TBA migration pathways. This hydrogeologic framework provides the basis for interpretation of: (1) the extents of the residual groundwater impacts, (2) attenuation of MTBE and TBA in groundwater, and (3) impacts to groundwater quality downgradient of the facilities.

1.2 HYDROGEOLOGIC CSM DEVELOPMENT

This report summarizes background information and documents the interpretations and conceptual hydrogeologic framework developed between approximately 2007 and 2016 through quarterly technical meetings between the car rental facilities and the NDEP. Under NDEP oversight, the responsible parties have investigated, remediated source areas, and are



continuing to monitor the extents of MTBE and TBA in groundwater downgradient of the former facility locations. Subsurface data collected by the CEMs are shared at the meetings and the data are used to update and refine or validate this CSM.

Starting in 2010, the data were compiled in a common database. On behalf of the environmental managers, CE2 Corporation maintains the database and prepares graphs, maps, and tables presenting the groundwater data. The data reports are available at http://www.ce2corporation.com/mccarran. In 2011, the CEMs retained AMEC Geomatrix, Inc. (Amec) to extract data from the common database and present it on large scale maps and a series of interpretive geologic cross-sections.

Initial draft interpretive geologic cross-sections, hydrostratigraphic interpretations, and delineation of the MTBE and TBA plumes were presented to the NDEP during the 9 May 2013 All Facilities meeting and updated for the 4 February 2014 meeting. Additional field investigation was subsequently performed and the hydrogeologic interpretations and interpretive geologic cross-sections were updated in 2015 and again in 2016. The most recent update is dated 28 September 2016 and was prepared by Langan Treadwell Rollo on behalf of the CEMs. The interpretive geologic cross-sections are included as Appendix A, and the presentation slides from the 9 May 2013 and 4 February 2014 meetings are included as Appendix B.

2.0 SITE DESCRIPTION

In this report, "the site area" is defined as the approximately 4,900 feet long and 700 feet wide area, trending west-southwest to east-northeast, that was investigated during the commingled plume project (Figure 1). The site area extends from McCarran Airport in the west to Maryland Parkway in the east and encompasses approximately 80 acres of land. The site area is overlain by McCarran Airport parking lots, public roadways, and commercial and residential developments. The locations of the facilities, the offsite investigation areas, the climate of the area, and land uses are described in this section.

2.1 LOCATION

The Payless, Avis, and National car rental and vehicle fueling operations were conducted at leaseholds in the northeastern portion of McCarran Airport. McCarran Airport and the site area are located in the south-central portion of the Las Vegas Valley (Figure 2).



The Payless and National facilities were on the west side of Rent-A-Car Road, and the Avis facility was on the east side. The car rental facilities addresses were 5175 (Payless), 5164 (Avis), and 5233 (National) Rent-A-Car Road. A number of other car rental facilities were historically located in this area as well and also were accessed from Rent-A-Car Road. The car rental facilities were demolished in 2007 and were replaced with the McCarran Airport Terminal 1 Economy Parking Lot (Figure 3).

East-northeast from the former Avis facility, the area between Paradise Road and Swenson Road was occupied by the Airport Inn (and subsequently a Howard Johnson's motel), several commercial properties, and the Palo Verde Circle residences. The Palo Verde Circle residences overlie the northernmost area investigated as part of the commingled plume investigations. The Howard Johnson's motel was demolished in 2012 and, as of 2017, is undeveloped.

Continuing in the east-northeastern direction from the former car rental facilities, the area between Swenson Boulevard and South Maryland Parkway is occupied by several residential neighborhoods. Commercial centers are located around the intersection of South Maryland Parkway and East Tropicana Avenue. Wilbur Street is within this area and is located approximately half-way between Swenson Road (Swenson Road is alternatively identified as the "McCarran Airport Connector") and South Maryland Parkway.

2.2 CLIMATE

The Las Vegas valley climate is arid and characterized by large temperature swings. Valley floor temperatures can exceed 120 degrees Fahrenheit, and there are typically more than 125 days per year where temperatures are 90 degrees Fahrenheit or warmer (Houghton et al, 1975). Conversely, in the Spring Mountains, west of the valley, winter temperatures are frequently below 32 degrees Fahrenheit. Average annual temperatures have increased from the mid-60s Fahrenheit in the 1980s, to approximately 70 degrees Fahrenheit in the 2000s (NOAA, 2016).

Annual average rainfall on the Las Vegas Valley floor is approximately 4 inches (NOAA, 2016). The Spring Mountains to the west receive more than 24 inches of precipitation each year. Rainfall patterns and the effects of these patterns on groundwater flow in the Las Vegas Valley groundwater basin are discussed in Section 5.



2.3 CURRENT AND FUTURE LAND USE

The land use in the locations of the former facilities is airport parking. Land uses over the downgradient portion of the commingled plume are residential and commercial. Development in the site area began in the 1960s, and the initial land uses remain relatively unchanged, despite the rapid population growth of the Las Vegas Valley. The population of Las Vegas increased from less than 500,000 in the 1980s to over 2 million in the 2010s (NOAA, 2016).

According to the City of Las Vegas Master Plan 2020, adopted 15 June 2000, while the overall population of Las Vegas is expected to continue to increase, land uses in the site area are expected to continue unchanged in the future. Future developments that could affect groundwater flow, such as subway systems or multi-story subterranean parking structures, although possible, are unlikely in this area, according to the Master Plan 2020.

3.0 HISTORICAL SITE INFORMATION

The Payless, Avis, and National facilities were formerly operated as car rental agencies with onsite vehicle fueling. A records review commissioned by the NDEP in 1996 identifies 13 sites with underground storage tanks (USTs), two additional sites with aboveground storage tanks (ASTs) and McCarran Airport's fuel farm in the vicinity of Rent-A-Car Road (HLA, 1996). Additional review of UST facilities in this area was performed by Broadbent in 2006 (Broadbent, 2006). The Payless (Allstate), Avis, and National car rental operations are listed in the 1996 review. By 2007, operations at these three car rental facilities had ceased and the USTs had been removed.

The history of the site area includes development of McCarran Airport and residential developments to the east-northeast, past Swenson Road by the mid-1960s; paving of Rent-A-Car Road and construction of car rental facilities in the 1980s; and operation of car rental agencies along Rent-A-Car Road through the 1990s and early 2000s (HLA, 1996). In 2006, 16 locations with registered USTs and 10 leaking underground storage tank (LUST) sites were located in the vicinity of Rent-A-Car Road (Broadbent, 2006). The detailed use history at the former Payless, Avis, and National car rental facilities, including UST systems, upgrades and removals, is provided in separate reports specific to each facility.

4.0 REGIONAL GEOLOGIC SETTING

The Las Vegas Valley is a structural depression formed by tectonic extension of the Basin and Range Province. The Spring Mountains west of the valley consist primarily of carbonate rocks



in a series of thrust sheets. In addition, the southern part of the Spring Mountains includes red cliffs formed from the Aztec Sandstone. The valley is bounded to the east by Frenchman Mountain, consisting primarily of Cambrian age sandstone overlying crystalline basement rock. The Las Vegas Valley and surrounding mountain ranges are shown on Figure 4.

4.1 GEOMETRY OF THE ALLUVIAL GROUNDWATER BASIN

While bedrock is exposed on the mountain ranges surrounding the valley, unconsolidated sediments cover the valley floor with thicknesses of up to 1,500 feet or more. In most areas of the valley, the thickness of the alluvium is at least 1,000 feet. The axis of the alluvial basin trends northwest to southeast and is approximately 40 miles long and 12 to 20 miles wide. Ground surface elevation of the valley is approximately 3,000 feet above mean sea level (msl) in the northwest and approximately 1,500 feet above msl in the southeast. The surrounding mountain ranges reach elevations of almost 12,000 feet above msl (NGWA, 1998).

4.2 COMPOSITION OF ALLUVIUM AND PLAYA DEPOSITS

The alluvial sediments of the valley consist primarily of clastic rocks eroded from the surrounding mountains. In the site area, water resource investigations have divided the sedimentary units into playa and alluvial fan deposits (Leising, 2004; Figure 5). The alluvial fan deposits generally consist of interbedded sandy gravels and the playa deposits consist of silts and clays. Caliche within the alluvial fan deposits is extensive and on a regional scale has been hypothesized to impede vertical groundwater flow.

4.3 QUATERNARY FAULTS

A series of east-dipping normal faults surfaces on the west side of the Las Vegas Valley (Figure 6). These active faults are mapped to the north of the site and are oriented north-south. The three active faults mapped closest to the site area include the Cashman Fault which runs adjacent to Eastern Avenue and the southern end of which is near Spring Mountain Road; the Valley View Fault adjacent to Las Vegas Boulevard, north of Sands Avenue; and the Decatur Fault, paralleling Decatur Boulevard, northward from the intersection of Decatur Boulevard and Hacienda Avenue (Page, Lundstrom, Harris et al, 2005).

5.0 REGIONAL GROUNDWATER CONDITIONS

The Las Vegas Valley hydrographic area (Hydrographic Basin 13-212) includes: (1) the alluvial groundwater basin formed by unconsolidated valley-fill sediments and (2) bedrock aquifers in the surrounding mountain ranges and underlying the valley-fill (Guillory & Brantley, 2015).



Figure 4 shows the areal extent of the Las Vegas Hydrographic Basin. The unconsolidated sediments consist primarily of clastic deposits from the surrounding mountain ranges. Lithostratigraphic units within the valley-fill are generally identified as coarser alluvial fan deposits or finer grained playa deposits. The unconsolidated sediments form a groundwater reservoir beneath the Las Vegas Valley from the shallow water table to the underlying crystalline basement rocks.

5.1 OCCURRENCE AND DEPTHS

Groundwater levels in the Las Vegas Valley range from just below ground surface (bgs) near the Las Vegas Wash to several hundred feet bgs near the western border of the alluvial basin. The groundwater table generally occurs within the upper 50 feet of most of the Las Vegas Valley floor (Lopes et al, 2006). Excessive groundwater pumping for municipal supply resulted in decreases of several hundred feet in the potentiometric surface elevations of the deeper groundwater aquifers in the 1970s. In the early 1990s, the deeper aquifer potentiometric surface elevations recovered by up to 70 feet as a result of an artificial recharge program (Figure 7).

5.2 GROUNDWATER FLOW DIRECTIONS AND GRADIENTS

Groundwater is recharged to the Las Vegas Valley groundwater basin primarily from the Spring Mountains. Groundwater flow within the valley-fill basin generally trends (1) southward from between the toe of the Kyle Canyon alluvial fan and the western base of the Sheep Range, and (2) eastward toward the Las Vegas Wash from the Spring Mountains. Groundwater beneath the Redrock alluvial fan, and in the piedmont areas to the south, generally flows in the east-northeastward. Groundwater exits the Las Vegas Valley groundwater basin south of Frenchman Mountain and flows toward Lake Mead (Figure 4).

Precipitation in the Spring Mountains recharges the bedrock aquifers. From the bedrock aquifers, groundwater flows into the unconsolidated valley-fill sediments (Domenico, Stephenson, and Maxey, 1964; Figure 8). In general, most groundwater entering the Las Vegas Valley groundwater basin is believed to be transmitted to the valley-fill aquifers through the carbonate rock units of the Spring Mountains (Plume, 1989). Within the valley-fill deposits, current-day groundwater flow paths are generally assumed parallel to surface topography, except where faults provide conduits for vertical flow. This flow pattern is used to explain the artesian conditions in many early water wells drilled on the valley floor.



The sustainable yield for the groundwater basin (excluding artificially recharged import water) is conservatively estimated at 25,000 acre-feet per year (Maxey and Jameson, 1948). Natural recharge estimates range from approximately 30,000 acre-feet per year to approximately 60,000 acre-feet per year (Malmberg, 1965; Harrill, 1976; Donovan & Katzer, 2000). Net well pumpage (i.e., excluding pumpage of artificially recharged water) decreased from approximately 85,000 acre-feet per year in the late 1960s and early 1970s, to a low of approximately 41,000 acre-feet in 1999 (Guillory & Brantley, 2015). From 2000 through 2015, net pumpage increased from approximately 44,000 to 75,000 acre-feet (Guillory & Brantley, 2015).

5.3 LVVWD HYDROSTRATIGRAPHIC UNITS IN THE MWFA

In the Las Vegas Valley Water District's (LVVWD) Main Well Field Area (MWFA), located approximately 6 miles north of the site area, the valley-fill has been subdivided into three hydrostratigraphic units: (1) Las Vegas Wash Aquitard, (2) Las Vegas Springs Aquifer, and (3) Duck Creek Aquifer (Donovan, 1996). Lithologic properties vary within each unit, so classification of the units as "aquifers," or "aquitards," is generalized. The hydrostratigraphic units were developed based on correlation to allostratigraphic units. Allostratigraphic units are defined by interpreted ages of accumulation.

The Las Vegas Wash Aquitard forms the uppermost few hundred feet of valley-fill sediments in the MWFA. This hydrostratigraphic unit consists of interbedded fine and coarse-grained deposits. Underneath the Las Vegas Wash Aquitard, municipal wells are screened within the Las Vegas Springs Aquifer; the depth of the upper boundary of this aquifer varies from near 100 to over 400 feet bgs. The Duck Creek Aquifer underlies the Las Vegas Springs Aquifer, extending from approximately 400 to 950 feet below ground surface. In general, the Las Vegas Springs Aquifer is coarser on the west side of the valley and becomes finer grained as it nears the Las Vegas Wash. An idealized representation of the MWFA hydrostratigraphy is shown in Appendix B (Amec, 2013, page 6).

5.4 BASIN-WIDE HYDROGEOLOGIC FRAMEWORK

Based on a limited data set, using driller well logs to estimate lithology, Plume (1989) developed a hydrogeologic framework for the Las Vegas Valley. Plume's study estimated that the upper approximately 50 feet of sediments in the area near McCarran Airport consists of thinly bedded fine and coarse-grained sediments, and that this lithologic unit thins toward the Las Vegas Wash to the east. Underlying this unit, Plume estimated an approximately 50 to



100 feet thick fine-grained unit. At between approximately 100 and 150 feet below ground surface, the upper surface of a regional coarse-grained unit (i.e., a principal aquifer) was estimated. Plume's fence diagram of the Las Vegas Valley subsurface is included as Figure 9.

5.5 SHALLOW GROUNDWATER SEPARATION FROM DEEPER AQUIFERS

The Las Vegas shallow aquifer system overlies the Las Vegas Wash Aquitard, other low permeability units, or in some areas near-surface aquifers (LVVWD, 1991). The shallow aquifer system is generally defined as the upper 30 feet of saturated sediments where groundwater occurs within 20 feet of ground surface (i.e., groundwater from 20 to 50 feet bgs). The shallow aquifer system may consist of perched groundwater overlying lower permeability units or may consist of horizontally migrating shallow groundwater that overlies deeper groundwater (LVVWD, 1991).

5.6 SOURCES OF RECHARGE TO SHALLOW SYSTEM AND DEEPER AQUIFERS

Prior to urbanization of the Las Vegas Valley and overdraft of the deeper aquifers, groundwater migrated upward from the deeper aquifers (1) into the shallow aquifer system or springs and seeps along fault surfaces, and (2) into the shallow aquifer system through discontinuities in the Las Vegas Wash Aquitard. Overdraft of the deeper aquifers in the 1970s discontinued most upward groundwater flow; however, excess landscape irrigation, leaking sewer and water supply lines, and other anthropogenic sources provided replacement sources of recharge to the shallow aquifer system (LVVWD, 1991). Accordingly, water table levels dropped through the 1980s in some areas, while no changes or increases in the water table elevation were recorded in other areas.

During the 1990s, the LVVWD conducted an artificial recharge program that injected surface water imported from Lake Mead into the Las Vegas Springs Aquifer. Potentiometric surface elevations for wells screened in the Las Vegas Springs Aquifer increased by tens of feet near the injection sites within the MWFA, but did not recover to pre-development levels (Leising, 2004; Figure 7). The effects of the recharge program on water levels in the shallow aquifer system appear to vary regionally.

5.7 REGIONAL WATER QUALITY

Shallow groundwater within the Las Vegas shallow aquifer system is typically saline, exhibiting total dissolved solids (TDS) concentrations between 1,000 and 7,000 mg/L (Huntington, 2016). High TDS is associated with high rates of evapotranspiration on the valley floor and



with dissolution of minerals within the shallow aquifer system (Leising, 2004). Deeper groundwater, generally below 100 feet bgs, typically exhibits much lower TDS concentrations.

Below the shallow aquifer, several groundwater facies have been identified, each with a different range of typical TDS concentrations. Groundwater from the Spring Mountain facies is generally documented as having TDS concentrations in the range of 350 to 500 mg/L.

6.0 SURFACE WATER BODIES

There are no perennial streams or rivers flowing from the Spring Mountains and onto the valley floor. The Las Vegas Wash, downstream of the waste water treatment plant, is the largest flowing surface water body in the Las Vegas Valley and is located approximately 6 miles east of the site area. Near the Las Vegas Wash, several smaller washes may exhibit occasional surface flows. Flows within the washes on the alluvial fans are generally the result of heavy rainfall and quickly infiltrate or evaporate. An unnamed wash intersects Gus Giuffre Road near Paradise Road. This unnamed wash has been culverted and routed through or around developments (Figure 10). A second unnamed wash was located near Lulu Avenue. This wash has also been culverted.

7.0 NEARBY WATER WELLS

For 2015, the Nevada Division of Water Resources (DWR) estimated gross groundwater pumpage from wells in the Las Vegas Valley at over 75,000 acre-feet. Most pumpage was from municipal wells, including those in the MWFA. The MWFA is approximately 6 miles north of the site area; however, historically, groundwater supply development included a municipal well center west of McCarran Airport which produced 5.0 million gallons per day (MGD) or 2,300 acre-feet per year. The DWR attributes approximately 6.5% of the total 2015 pumpage, or nearly 5,000 acre-feet, to domestic wells (Guillory & Brantley, 2015). DWR estimates 4,489 active domestic wells in the Las Vegas Valley basin (Guillory & Brantley, 2015).

Water supply well surveys were conducted for the site area in 1995, 2008 and 2016. The 1995 survey by Broadbent reviewed DWR records and identified wells #16691 and #15760 within ½ mile of the Avis facility. The 1995 report concluded that neither of the wells were downgradient and, therefore, were unlikely to be impacted. The 2008 survey was conducted using the LVVWD FacilityView program and field reconnaissance and found four wells approximately 5,000 feet east of the distal end of the plume. The 2016 survey included reevaluation of the LVVWD database and confirmed the 2008 findings (Broadbent, 2016; Figure



11). In addition, Amec (2013) reviewed DWR records to obtain lithologic and historical water quality data for the site area. The results of that effort are described in Section 8.3.

8.0 SITE GEOLOGY

The geology of the site is assessed primarily on the recorded observations of geologists and engineers during subsurface activities related to the investigation and remediation of the commingled plume. The monitoring well database for the commingled plume includes 168 monitoring wells and associated boring logs. The geology of the site area was also investigated during drilling of temporary borings and remediation wells, and during excavations, and many of the reports of these activities include descriptions of the geology observed during the work.

8.1 SURFACE GEOLOGY

To augment the site-specific observations, Geo Blue reviewed a geologic map of the Las Vegas Valley (Figure 6). Surficial geology of the northeastern portion of McCarran Airport, including the three former car rental leaseholds, is mapped by the USGS as younger quaternary alluvium (Qay). Sediments within the wash intersecting Gus Giuffre Road, adjacent to the former Payless and Avis operations are mapped as youngest quaternary alluvium (Qayy). The quaternary alluvium is classified as gravelly fan deposits. East of Swenson Street, the USGS maps surficial geology as undivided fine-grained sediments of the Las Vegas Valley, of quaternary and potentially tertiary age (QTs) (Page, Lundstrom, Harris, et al., 2005). Presumably, based on depositional ages, Qayy overlies Qay, which in turn overlies QTs. The thicknesses of the units are not specified in this USGS geologic report.

8.2 LITHOLOGY OF LOGGED SEDIMENTS

Observed lithology documented in the project reports included clays, silts, sands, gravels, and caliche. The caliche is a secondary deposition, observed primarily within the sands and gravels. In general, sands, poorly graded sands (i.e., sand-silt or sand-clay mixtures), gravels, poorly graded gravels (i.e., gravel-silt or gravel-clay mixtures) predominate the upper 30 feet of many boring logs. Sediments below 30 feet bgs, to the maximum explored depth of the investigations or approximately 80 feet bgs, were predominated by clays and silts. Sand and gravel beds several feet thick were recorded between 30 and 80 feet bgs on many of the logs for deeper borings. Logs generated for the upper 25 to 30 feet in the site area west of Swenson Street frequently include thinly bedded silty sands and gravels. In the upper approximately 30 feet of borings drilled east of Swenson Street, relatively finer grained



deposits were more frequently observed, including clayey sands, silty sands, clayey gravels, and silty gravels.

As part of the downgradient and deeper groundwater investigations conducted from 2009 through 2014 (OGI, 2009; Broadbent, 2010; Broadbent, 2012; OGI, 2014), deeper borings were drilled. Throughout the site area, clays and silts, including a red or reddish-brown clay, were frequently observed below 30 feet bgs. Although the predominant lithology is fine grained, gravel and sand beds up to several feet thick were reported in a number of logs.

8.3 DEEPER SITE GEOLOGY

The investigations performed in the site area extended to a maximum depth of approximately 80 feet bgs. There are approximately 25 wells with screens that are within the range of 60 to 80 feet bgs. To further evaluate the deeper site lithology, below 80 feet bgs, Amec (2013, 2014) obtained driller's well logs for former water supply wells in or adjacent to the site area. DWR records identified 12 inactive or destroyed wells installed between 1943 and 1962 in the NE quadrant, of the NW quadrant, of Section 27, Township 21 south, Range 61 east, Las Vegas Valley hydrographic area (i.e., wells with identification beginning with 212 S21 E62 27 BA). From these 12 wells, 9 drillers logs provided sufficient detail to estimate sediment lithology. Using a visual comparison of the logs, Amec concluded that the sediment type observations recorded on the logs confirmed the differentiation between the upper 30 feet bgs and deeper site lithology (Amec, 2014). The logs also suggest that the predominantly finegrained lithology continues downward until at least approximately 100 to 120 feet bgs.

8.4 Interpretive Geologic Cross Sections

Cross-sections oriented parallel and perpendicular to the commingled plume axis were prepared to provide a three-dimensional representation of the site subsurface. To generate the cross-sections, Unified Soil Classification System (USCS) soil types, well construction, groundwater chemistry, former site boundaries, remedial systems, former excavations, major roadways, and key surface features were geocoded in ArcGIS, then plotted on maps and vertical profiles. A data entry format was developed and agreed to by OGI, Broadbent, Converse, and Amec. Prior to entry into the geodatabase, data was reviewed and validated.

Lithologic observations had been recorded over a period of years and by different field geologists, who were employed by different companies. Accordingly, professional judgement was required to distill the observations described on the boring logs into the USCS system. In addition, drilling methods and sample collection frequency appears likely to have influenced



the geology interpreted in the investigation reports. Specifically, logs prepared for borings drilled using a hollow-stem auger (HSA) rig were typically based on collection of 1.5 feet of core per 5 feet of boring. This sampling rate was frequently reduced further by poor recovery when caliche was encountered. Conversely, where sonic drilling techniques were applied, continuous cores were retrieved, typically over 20-foot intervals. Many of the logs for borings drilled using HSA techniques do not record any thinly bedded gravel or sand deposits; whereas such potential groundwater migration pathways were generally observed when continuous cores were collected. Accordingly, interpretations in the cross-sections consider the relative data quality of the boring logs. The cross-sections are included in Appendix A.

West of Paradise Road

Interpretations of lithology west of Paradise Road are included on cross-sections A-A', B-B', and C-C'. Multiple borings and wells were drilled and excavations were performed in the upper 30 feet west of Paradise Road. Fewer deeper borings were drilled in this area. The upper 30 feet is coarse grained, and finer grained sediments predominate from 30 to approximately 60 feet bgs. Thinly bedded sand or gravel units were observed below 30 feet bgs. The upper 30 feet of cross-section B-B' is relatively finer-grained than the upper 30 feet of cross-section A-A'. Cross-section B-B' is south of cross-section A-A'.

Between Paradise Road and Swenson Street

Cross-sections A-A', B-B', D-D', E-E', and F-F' are within this area. This area includes the subsurface below the former Howard Johnson's motel property where remediation systems were installed. Shallow and deeper borings were drilled in this area. Coarser grained sediments predominate the upper 30 feet and finer grained sediments were reported between 30 and 60 feet bgs.

Between Swenson and Wilbur Streets

Cross-section A-A' is within this area. Shallow borings were typically drilled to approximately 30 feet bgs and the logs report coarse-grained sediments, predominated by sands. Few deeper borings were drilled in this area. OGI reported silts in OMW-48-45 from 22 feet bgs to 48 feet bgs, and silty sands deeper in OMW-48-65. These observations are consistent with the general trends reported elsewhere in the site area for sediments below 30 feet bgs.

Between Wilbur Street and Maryland Parkway



Cross-sections A-A', G-G', H-H', and I-I' are within this area. Three transects of multi-depth wells were drilled in between Wilbur Street and Maryland Parkway to investigate shallow and deeper groundwater. Well OMW-79-79, located between Lulu Avenue and University Plaza, was drilled to 80 feet bgs. Detailed logging was performed as part of the investigations; continuous cores were obtained for the borings, and some of the borings were advanced using sonic drilling methods. Sands and gravels predominate the upper 30 feet, and clays were observed from 30 to approximately 60 feet bgs. Thinly-bedded sands and gravels were observed below 30 feet in the deeper borings. Cross-section A-A' is data-driven in the area west of Paradise Road, whereas the cross-section is more interpretive in this area to present the additional information collected during the drilling programs in this portion of the site area.

9.0 SITE HYDROGEOLOGY

As detailed in Subsections 9.1 through 9.3, the shallow groundwater zone at the site is hydraulically and chemically differentiated from the underlying deeper zone. Because MTBE and TBA concentrations in the shallow zone have attenuated while MTBE and TBA concentrations persist in the deeper zone, these two hydrostratigraphic zones (i.e., the shallow zone and the deeper zone) need to be understood on the site-scale.

9.1 Depth to Groundwater

The depth to groundwater in the site area west of Paradise Road, beneath the locations of the former car rental operations, ranged from 13.10 to 19.00 feet bgs during the Fourth Quarter 2016 and from 13.71 to 18.56 feet bgs during the Fourth Quarter 2017. In general, the depth to water beneath the site area decreases from west to east.

Decreasing Depth Toward Maryland Parkway

The depth to groundwater near Maryland Parkway is approximately 5 feet less than the depth to groundwater near Paradise Road (Amec, 2014). Appendix B (Amec, 2014, page 16) compares ground surface elevations to groundwater surface elevations at various distances downgradient from the former facility locations.

Decreasing Depth Over Time

The depths to groundwater beneath the various portions of the site area have decreased over the monitoring period. Between 1995, when monitoring began, and 2017 the depth to groundwater decreased by approximately 5 feet.



9.2 GROUNDWATER FLOW DIRECTIONS AND GRADIENT

Groundwater elevation contours for Fourth Quarter 2015 are plotted on the map included with the interpretive geologic cross-sections. The groundwater table surface west of Paradise Road dips northeastwardly. East of Paradise Road, the inferred horizontal groundwater flow direction is to the east-northeast. Over the monitoring period, the interpreted aggregate direction of horizontal groundwater flow has been consistently to the east-northeast.

On average in the site area, the water table gradient is approximately 0.01 ft/ft to the east-northeast. Near Paradise Road, the gradient steepens to approximately 0.02 ft/ft, and from approximately Swensen Street to Maryland Parkway, the magnitude of the gradient is approximately 0.007 ft/ft.

The potential presence of vertical gradients was evaluated by Broadbent during the All Facilities NDEP meetings conducted in 2009 and 2010, and by OGI (2009). In some analyses, there appeared to be an upward gradient between groundwater at approximately 60 feet bgs and groundwater at approximately 45 bgs, and a downward gradient between groundwater at approximately 30 feet bgs and groundwater at 45 feet bgs. Conceptually, these trends could be explained by the conceptual model for idealized groundwater flow in the basin. In addition, the regional recharge project injected groundwater into the deeper producing aquifers, and excess irrigation water and leaking pipes infiltrate groundwater into the shallow aquifer, both of which might be expected to support such trends. OGI estimated vertical gradients, if present, to be relatively low.

9.3 AMBIENT WATER QUALITY

Groundwater samples collected between 2012 and 2017 were analyzed for TDS. TDS concentrations in site monitoring wells ranged from 184 to 8,042 mg/L. Many of the samples collected from shallow groundwater contained greater than 2,000 mg/L TDS. High salinity in shallow groundwater is a regional feature and was anticipated.

Groundwater samples were also analyzed to evaluate intrinsic biodegradation of petroleum compounds, including MTBE and TBA. Parameters monitored at the site included dissolved oxygen (DO), oxidation-reduction potential (ORP), pH, conductivity, temperature, nitrate, sulfate, and ferrous iron. Investigation of metals in groundwater was performed as part of the remedial pilot testing performed by Broadbent in 2010 (Broadbent, 2010).



Ambient groundwater appears to be aerobic (>1.0 mg/L D0). Petroleum compounds and volatile organic compounds (VOCs) were generally not detected in ambient groundwater samples. Further review of ambient water quality, and comparison to groundwater conditions within the commingled plume area is outside the scope of this report and will be discussed in a report of MTBE fate and transport of the offsite MTBE plume.

9.4 HYDROSTRATIGRAPHY

The hydrostratigraphy of the site was interpreted based on the lithologic observations described in Section 8.0, overlain with groundwater chemical data. This approach is similar to the methodology used by Leising (2004) to develop hydrostratigraphic units for the MWFA; however, sequence stratigraphy to develop allostratigraphic interpretations was not attempted. The site hydrostratigraphy is divided into two units: a shallow zone and a deeper zone. The shallow zone is characterized by coarser-grained deposits, higher transmissivity, and high TDS concentrations. The shallow zone, which appears to correlate with the sandy aquifer referred to by the LVVWD as the Shallow Aquifer System, is hydraulically and chemically differentiated from the underlying deeper zone.

The deeper zone is characterized by finer-grained deposits, lower transmissivity, and the presence of laterally extensive beds of sands and gravels. The coarse-grained units, likely deposited as channel deposits during aggradation of the alluvial fan, appear to have the potential to sustain relatively high groundwater velocities.

The Interpretive Geologic Cross-Sections (Langan, 2016) depict the interpreted boundary between the Upper and Lower Hydrostratigraphic units (HSUs). The HSU boundary is at approximately 30 feet bgs, across the entire site area.

10.0 PREFERENTIAL PATHWAYS

Natural and anthropogenic preferential pathways for MTBE and TBA migration have been evaluated as part of the site investigation efforts. The Upper HSU generally consists of sandy deposits, so preferential pathways might include deeper buried utilities and improperly destroyed water supply wells. To date, such features have not been identified in the site area.

Within the Lower HSU, thinly bedded gravels and sands have acted as migration pathways for MTBE and TBA. Detailed borehole logging, including sonic drilling techniques to recover continuous soil cores, and depth-discrete groundwater sampling, found MTBE and TBA concentrations in offsite groundwater in thin sandy or gravelly units located within the Lower



HSU (OGI, 2009; Broadbent, 2012). These thin lithostratigraphic units occur at various depths. Based on the understanding of the regional depositional history, the sandy and gravelly lenses may be interconnected and are not likely to be laterally continuous.

The thin beds of gravel and sand were frequently described as loosely-compacted gravels with clay and sand (OGI, 2014: Log OMW-79-79) or as well graded gravel with silt and sand (Broadbent, 2013: Log OMW-75-76). On many logs, the field geologist recorded caliche deposits within or above the thinly bedded gravels and sands.

Fault planes have also been regionally identified as potential pathways for vertical groundwater flow, potentially including flow between the two HSUs in the investigation area (Leising, 2004). Leising (2004) hypothesized that the overdraft conditions, which followed development of Las Vegas Valley groundwater resources for water supply, may have resulted in fault planes becoming pathways for downward migration of shallow groundwater. Accordingly, there is the potential that MTBE and TBA may have migrated from shallow to deeper groundwater via the fault plane pathway. After the regional groundwater recharge program was implemented in the early 1990s, groundwater migration between deeper water resources and the shallow aquifer is anticipated to have been generally reduced and, in some areas, may have been restored to pre-development, upward flow conditions.

11.0 RELEASE SOURCE/UST SYSTEMS

One LUST gasoline release is reported on 21 December 1999 at the Payless (Allstate) facility in the NDEP Project Tracking database. At the Avis facility, three LUST gasoline releases are reported in the database: 1 January 1990, 14 November 2001, and 8 August 2007. And, at the National facility one LUST gasoline release is reported on 28 October 2002 in the database. Demolition of the three facilities in 2007 was completed after the UST systems were removed.

Broadbent (1995) reviewed Clark County Fire Department (CCFD) and Clark County Health Department (CCHD) files and identified UST operators in the site vicinity, including a UST at the Airport Inn, formerly located east of Paradise Road. Harding Lawson and Associates (1996) conducted aerial photograph reviews, regulatory agency record reviews, and a site reconnaissance to evaluate potential sources, receptors, and migration pathways for free product on the groundwater table near the facilities.



Broadbent (2006a, 2006b) conducted regulatory agency reviews, reconnaissance, and collected groundwater samples downgradient of potential additional contributors to the commingled plume. No additional contributors to the commingled plume were confirmed.

12.0 LNAPL

Historically, light non-aqueous phase liquid (LNAPL) was reported at the individual facilities and offsite in monitoring well MW-13 (since renamed HJMW-22) located east of Paradise Road (Broadbent, 1995). LNAPL from the Payless facility is believed to have migrated offsite onto the northern portion of the Avis leasehold, cross-gradient of the Avis UST system. Evaluation of historical LNAPL extent at each facility is not included in the scope of this hydrogeologic CSM for the three facilities.

In the offsite area, remediation was performed at the former Howard Johnson's motel location through the early 2000s. As of 2017, no mobile or migrating LNAPL was present in any of the site monitoring wells. Based on petroleum concentrations in groundwater, it is unlikely that residual LNAPL (i.e., non-migrating and non-mobile) remains in the offsite areas.

13.0 CONTAMINANTS OF CONCERN

The primary contaminant of concern common to the three facilities has been MTBE and TBA as a degradation product. The releases were identified as gasoline releases, and elevated benzene, toluene, ethylbenzene, and xylenes (BTEX) were historically detected in groundwater. In general, petroleum compounds other than MTBE and TBA did not migrate significantly beyond the areas affected by LNAPL.

14.0 SOIL IMPACTS

Soil near the groundwater table in the area of historical LNAPL extent was likely impacted when LNAPL was present; however, LNAPL was no longer present in any monitoring wells as of the Fourth Quarter 2017. MTBE and TBA do not readily adsorb to soil (i.e., have low organic carbon partition coefficients (Koc)) and are highly soluble. Accordingly, soil impacts would consist primarily of BTEX compounds and other petroleum hydrocarbons. Through the Fourth Quarter 2017, elevated groundwater levels have placed groundwater in contact with soil that would have been impacted when LNAPL was present. If the soil impacts had persisted, then shallow groundwater would be affected. No MTBE, TBA, or other gasoline compounds were reported during the Fourth Quarter 2017 in any of the shallow groundwater wells screened



within the Upper HSU. Soil in the commingled plume area is not likely to be impacted by petroleum hydrocarbons, MTBE, or TBA.

Soil remediation was performed at the individual Payless, Avis, and National facilities, and residual onsite impacts will be summarized by the respective CEMs. Soil remediation activities at the facilities typically included over-excavation and offsite disposal of contaminated soil and soil vapor extraction.

15.0 SOIL GAS IMPACTS

MTBE and TBA are highly soluble and correspondingly have relatively lower Henry's Law constants, indicating that the potential for MTBE or TBA volatilization from liquid to vapor phase is limited. At the request of the NDEP, Broadbent (2009) conducted a soil gas survey within the site area. Six soil gas samples were collected and analyzed for total petroleum hydrocarbons (TPH) as gasoline (TPHg), BTEX and MTBE. MTBE was not detected in the soil gas samples. TPHg, benzene, toluene, and xylenes were detected, and the results were included in the 2009 Human Health Risk Assessment Update (Synergy, 2009). Synergy (2009) concluded that the relatively low petroleum compound concentrations reported in soil gas did not pose an unacceptable risk (i.e., calculated cancer risk less than the United States Environmental Protection Agency threshold of 1E-06 and hazard quotient less than 1.0). Because petroleum concentrations in shallow groundwater were below the NDEP action levels, soil gas in the commingled plume area as of Fourth Quarter 2017 was not likely impacted by petroleum hydrocarbons, MTBE or TBA.

16.0 GROUNDWATER IMPACTS

MTBE and TBA concentrations in groundwater are contoured utilizing the fourth quarter groundwater monitoring data each year. The most recent isoconcentration maps were prepared using the Fourth Quarter 2017 monitoring data, collected in November and December 2017. The Fourth Quarter 2017 isoconcentration maps prepared by CE2 Corporation, on behalf of the CEMs, are included in Appendix C. The subsections below describe the conceptual model of residual MTBE and TBA impacts in groundwater. The historical MTBE and TBA concentrations in groundwater in the site area are documented in the groundwater monitoring reports, initially prepared for each facility, and later prepared on behalf of the three CEMs. In the late 1990s, MTBE concentrations in groundwater monitoring wells were as high as 100,000 ug/L to 192,250 ug/L. Natural attenuation is reducing the extent and magnitude of MTBE and TBA groundwater impacts over time. MTBE and TBA



concentrations measured during the Fourth Quarter 2015 (shown on the cross-sections in Appendix A), and during the Fourth Quarter 2017 (Appendix C) are summarized in the subsections below.

16.1 Source Areas at the Facilities

In or near the former facility locations, Fourth Quarter 2017 groundwater monitoring detected up to 2,000 ug/L MTBE in well MW-16-60 (National facility); 1,100 ug/L MTBE in well PMW-17-52 (Payless facility); and 210 ug/L MTBE in well AVMW-50-35 (Avis facility). The source area residual groundwater impacts did not appear to extend east of approximately Paradise Road. As of Fourth Quarter 2017 source area remediation was ongoing, and, consequently, MTBE and TBA concentrations at the former facility locations are expected to decrease. Each facility is addressing source area concentrations independently.

16.2 DOWNGRADIENT AREAS

The cross sections included in Appendix A depict contoured MTBE data collected during the Fourth Quarter 2015. MTBE concentrations in groundwater decreased from 2015 through 2017, and the extent of the MTBE and TBA plumes further receded. As of Fourth Quarter 2017, MTBE and TBA concentrations in the Upper HSU were below the NDEP action level of 200 ug/L. Also, as of Fourth Quarter 2017, in the downgradient area, near Wilbur, South Young, and South Turner Streets, MTBE persisted in groundwater between approximately 50 feet bgs and 70 feet bgs at concentrations above the action level, up to 1,400 ug/L. MTBE concentrations in deeper wells OMW-43-75, OMW-72-77, and OMW-79-79 delineated the vertical extent of the plume, to below the NDEP action level. At that time, groundwater in the zone with residual MTBE impacts was generally anaerobic (DO less than 1.0 mg/L).

Along Maryland Parkway, MTBE and TBA concentrations in monitoring wells OMW-68, OMW-70, and OMW-71, decreased and were below the NDEP action level in Fourth Quarter 2017. These results suggest that the plume is receding.



17.0 REFERENCES

Amec. 2013. Regional Geologic Setting and Soil Boring Log Compilation. Presentation at the 9 May 2013 Former Rental Car Facilities Meeting.

Amec. 2014. Preliminary Conceptual Site Model. Presentation at the 4 February 2014 Former Rental Car Facilities Meeting.

Broadbent & Associates, Inc. 1995. Results of Additional Characterization and Third Quarter 1995 Monitoring. Avis Rent-A-Car, Inc., 5164 Rent-A-Car Road, Las Vegas Nevada. October 25.

Broadbent & Associates, Inc. 2006a. UST Proximity Report And Work Plan for Further Characterization Of The Avis/National/Payless Dissolved MTBE Commingled Plume In Groundwater, Las Vegas, Nevada. August 14.

Broadbent & Associates. 2006b. Results of Environmental Database Review, Area Reconnaissance and Case File Reviews for Surrounding Sites and Work Plan for Further Characterization of the Commingled MTBE Plume in Groundwater, Las Vegas, Nevada. November.

Broadbent & Associates, Inc. 2009. Soil Gas Survey Summary Report, Former Avis Rent A Car System, Inc. Facility, 5164 Rent-A-Car Road, McCarran International Airport, Las Vegas, Nevada. 28 August.

Broadbent & Associates, Inc. 2010. Results of Intermediate Groundwater Zone Characterization and Work Plan for PulseOx Pilot Test. Avis Rent A Car System, LLC, Facility. Las Vegas, Nevada. 20 August.

Broadbent & Associates, Inc. 2012. Additional Downgradient Characterization Report. Avis Rent A Car System, LLC, Facility. Las Vegas, Nevada. 26 January.

Broadbent & Associates, Inc. 2013. Lithologic Cross Section: Far Downgradient Investigation, Presentation to Nevada Department of Environmental Protection. 5 February.

Broadbent & Associates, Inc. 2016. Sensitive Receptor Survey. Vicinity of Former Avis, National and Payless Car Rental Facilities, McCarran International Airport, Las Vegas, Nevada. 5 October.

Brothers, Kay and Katzer, Terry. 1988. Ground-water chemistry changes resulting from stressed aquifer systems in Las Vegas Valley, Clark County, Nevada. Las Vegas Valley Water District and the Nevada Division of Environmental Protection, Carson City, Nevada.

Converse Consultants. 2009. Additional Site Investigation Report. Former National Car Rental Facility, 5233 Rent-A-Car Road, Las Vegas, Nevada. 19 January.



Converse Environmental Consultants Southwest, Inc. 1995. Site Characterization/Monitoring Well Installation, Avis Rent-A-Car, 5164 Rent-A-Car-R0ad, Las Vegas Nevada. 16 March.

Domenico, P.A., Stephenson, D.A. and Maxey, G.B. 1964. Ground Water In Las Vegas Valley: Nevada Department of Conservation and Natural Resources, Water Resources Bulletin No. 29.

Donovan, David J. 1996. Hydrostratigraphy and allostratigraphy of the Cenozoic alluvium in the northwestern part of Las Vegas Valley, Clark County, Nevada. University of Nevada, Las Vegas. Master's Thesis. August.

Donovan & Katzer. 2000. Hydrologic implications of greater ground-water recharge to Las Vegas Valley, Nevada: Journal of the American Water Resources Association, v. 36.

Guillory, John, P.E., & Brantley, Desiree: State Of Nevada Department Of Conservation And Natural Resources, Division Of Water Resources (DWR), Jason King, P.E. State Engineer, Las Vegas Valley (Hydrographic Basin 13-212) Groundwater Pumpage Inventory Calendar Year 2015.

Harding Lawson Associates (HLA), 1996, Results of Records Review, Rent-A-Car Road & Paradise Road Vicinity; Palo Verde Road Area, Las Vegas, Nevada. 11 September.

Harrill, James R. 1976. Pumping and Ground-Water Storage Depletion in Las Vegas Valley, Nevada. 1955-74: Nevada Department of Conservation and Natural Resources, Water Resources Bulletin No. 44.

Houghton, J.G., Sakamoto C.M., 1975. Nevada's Weather and Climate. Nevada Bureau of Mines and Geology Special Publication 2, 78p.

Huntington, Jena. 2016. Conceptual Understanding and Groundwater Quality of the Basin-Fill Aquifer in Las Vegas, Valley, Nevada. United States Geological Survey, Professional Paper 1781.

Johnson, Michael, et al., (Southern Nevada Water Authority). 1998. Hydrogeology and Geology of the Las Vegas Valley, Clark County, Nevada, Field Trip Guide Book. 16 December.

Las Vegas Valley Groundwater Management Program website. 2013. water level data, http://www.lasvegasgmp.com/html/telemetry_index.html. April.

Las Vegas Valley Water District. 1991. The Shallow Aquifer System in Las Vegas Valley, Nevada. August.



Leising, Joseph F. 2004. Chemical Conditions in the Primary Producing Aquifers and Portions of the Shallow Groundwater System of the Las Vegas Valley in 2000. Southern Nevada Water Authority. 7 March.

Malmberg, Glenn T. 1965. Available Water Supply of the Las Vegas Ground-Water Basin, Nevada. United States Geological Survey Water-Supply Paper 1780.

Maxey, G.B and Jameson, C.H. 1948. Geology and Water Resources of Las Vegas, Pahrump, and Indian Springs Valleys, Clark and Nye Counties, Nevada: State of Nevada Office of State Engineer, Water Resources Bulletin No. 5.

Morgan, D.S., and Dettinger, M.D. 1996. Ground-water conditions in Las Vegas Valley, Clark County, Nevada; Part 2, Hydrogeology and simulation of ground-water flow: U.S. Geological Survey Water-Supply Paper 2320–B, 124 p.

National Ground Water Association (NGWA). 1998. Hydrogeology and Geology of the Las Vegas Valley, Clark County, Nevada. December 16.

OGI Environmental LLC. 2009. Additional Plume Delineation and Remediation Equipment Evaluation Report, Former Payless Car Rental, 5175 Rent-A-Car Road, Las Vegas, Nevada. 6 February.

Page, Lundstrom, Harris, et al. 2005. Geologic and Geophysical Maps of the Las Vegas 30' X 60' Quadrangle, Clark and Nye Counties, Nevada, and Inyo County, California. United States Geological Survey. Scientific Investigations Map 2814.

Pavelko, M.T., Wood, D.B., and Laczniak, R.J. 1999. Las Vegas, Nevada: in Galloway, D.L., Jones, D.R., and Ingeb-ritsen, S.E., eds., Land subsidence in the United States: U.S. Geological Survey Circular 1182, p. 49–64.

Payne, Fred (Arcadis). 2011. California The Continuing Evolution of Groundwater Remediation Hydrogeology, Groundwater Resources Association Webcast. 23 May.

Plume, R.W. 1989. Ground-water conditions in Las Vegas Valley, Clark County, Nevada—Part I, Hydrogeologic framework: U.S. Geological Survey Water-Supply Paper 2320–A, 15 p.

Stachelski, Chris and Gorelow, Andy. Original edition compiled by Skrbac, Paul. 2016. The Climate of Las Vegas. National Oceanic and Atmospheric Administration. 14 January.

Synergy Toxicology. 2009. Human Health Risk Assessment Update, Avis/National/Payless Commingled Groundwater Plume, Las Vegas, Nevada. February.


Lopes, Thomas J., et al. 2006. Water-Table Levels and Gradients, Nevada, 1947-2004. United States Geological Survey. Scientific Investigations Report 2006-5100.




Wood, D.B. 2000. Water use and associated effects on ground-water levels, Las Vegas Valley and vicinity, Clark County, Nevada, 1980–95: Nevada Division of Water Resources, Water-Resources Information Report 35, 101 p.


Zikmund. 1996. Extent and Potential Use of the Shallow Aquifer and Wash Flow in Las Vegas Valley, Nevada: Southern Nevada Water Authority.

FIGURES









From Google Earth and Google Maps, Viewed on 28 August 2018

DRAFT Hydrogeologic Conceptual Site Model Report	Current Site Uses – McCarran Economy Parking
Geo Blue Consulting	Figure 3
	28 August 2018




Figure 5. Las Vegas Valley Physiographic Features and Groundwater Flow Directions.

From Liesing, 2004	
DRAFT Hydrogeologic Conceptual Site Model Report	Las Vegas Valley Physiographic Features and Groundwater Flow
Geo Blue Consulting	Figure 4
	28 August 2018





Figure 13. Hydrostratigraphic Units in the Las Vegas Valley (after Donovan, 1996).

From Liesing, 2004		
DRAFT Hydrogeologic Conceptual Site Model Report	Las Vegas Valley Hydrostratigraphic Units	
Geo Blue Consulting	Figure 5	
	28 August 2018	



From USGS, National Geologic Map Database, 2018		
DRAFT Hydrogeologic Conceptual Site Model Report	Surface Geology in the Site Vicinity	
Geo Blue Consulting	Figure 6	
	28 August 2018	




Figure 11. Change in the Potentiometric Surface of the Important Producing Aquifers, 1990 to 1999.

From Liesing, 2004	
DRAFT Hydrogeologic Conceptual Site Model Report	Change in Potentiometric Surface, 1990 to 1999
Geo Blue Consulting	Figure 7
	28 August 2018





Figure 9. Idealized flow system, Las Vegas Valley.

Idealized Groundwater Flow System, Las Vegas Valley
Figure 8 28 August 2018



From Plume, 1989	
DRAFT Hydrogeologic Conceptual Site Model Report	Fence Diagram Showing Lithology and Water-Bearing Properties
Geo Blue Consulting	Figure 9
	28 August 2018




November 2008




From Google Maps, 2018

DRAFT Hydrogeologic Conceptual Site Model Report	Surface Water Bodies – Unnamed Wash				
Geo Blue Consulting	Figure 10				
Oeo blue Corisuining	28 August 2018				



APPENDIX A INTERPRETIVE GEOLOGIC CROSS-SECTIONS



APPENDIX B

PRESENTATION SLIDES FROM THE 9 MAY 2013 AND 4 FEBRUARY 2014 MEETINGS



Regional Geologic Setting and Soil Boring Log Compilation

Prepared for the May 9, 2013 Former Rental Car Facilities Meeting




CSM Efforts Since February 2013 Meeting

- Completed digitization of well logs
- Plotted log and chemistry data on cross-sections
- Compiled regional studies (SNWA, LVVWD, USGS, and others)
- Obtained limited data from NDWR well databases

Regional Groundwater Flow Directions and Hydrologic Features





- The Rental Car Plume is adjacent to (or on top of?) the unnamed wash south of Flamingo Wash
- The LVVWD Main Well Field is approximately 6 miles north of the sites, adjacent to Hwy 95 and West of the I-15



Regional Geology

- Coarser alluvial fan deposits
- Finer playa deposits
- >1,500 ft of unconsolidated sediments

Las Vegas Valley Basin









Figure 1-7, -- Generalized Geologic Cross Section of the Las Vegas Valley.

- 1,500 ft of unconsolidated sediments
- Alluvial fan deposits interfingered with playa deposits
- Water table intersects surface at the Las Vegas Wash


Major Stratigraphic Units (Leising, 2004)





Spring Mountains


- No distinct lithologic boundaries
- Hydrostratigraphic definitions include:
- Age of sediments
- Water quality (TDS)



Bedrock

Generalized Water Uses by Depth





Domestic and irrigation use of shallow groundwater

- Lower well yields and higher TDS in upper 100+ ft.
- Older wells screened in both shallow groundwater and Las Vegas Springs Aquifer

Deeper Lithologic Information For the Site

chi





- of supply wells started at 40 ft bgs. Screened intervals
- 1962 in NE1/4 of NW1/4 of Section 27 locations circled in 12 wells installed between 1943 to represented by

Edacienda Ave

0

E Dalton Dr S

E De Met Dr

0

E Laramon Dr.


P O P

E Bell D

0

				- Continue of the continue of		
well_log	well_finis	date_log_r	depth_dril	depth_case	top_perf	bottom_per
51621	6/1/1943	5/3/1944	338	0	0	0
51539	9/10/1945	10/20/1945	909	603	512	603
56160	10/30/1949	<nul></nul>	73	0.2	0	0
56146	9/1/1950	<nul></nul>	75	23	0	0
56171	10/1/1950	<nul></nul>	75	23	0	0
56145	12/20/1951	<nul></nul>	100	23	0	0
56144	7/1/1953	<nul></nul>	205	29	0	0
56155	11/18/1953	<nul></nul>	190	125	61	125
56127	4/17/1954	<nul></nul>	150	09	0	0
56161	1/6/1955	<nul></nul>	100	100	20	100
5394	7/19/1960	9/9/1960	300	300	120	300
6657	4/12/1962	7/23/1962	250	250	09	250

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



ameco

Address Paridise Valley Rd & Bond Rd. AddresP.O.Box 2081 Las Vegaslic No.137. Driller Douglas Slagle Clark Location of well: 1/5 1/4 M/1/4 Sec. 2 7, 72 1 M/S, R 6 1 E, in Owner Roy Kaufman

or Lot # 8of the Bates Acreage (Corner of Bond Ed. & Paridise Eds.) . Weight of casing per linear foot 9.91 ... Total depth of well ... 205. Water will be used for....Domestic Size of drilled hole......

Diameter and length of casing 8"3/16 I.D. 1186d 67 Et. of Gasing in Mell (Casing 12" in diameter and under give inside diameter.) Temp. of water......Cool. Thickness of casing 12 Gage

If flowing well give flow in c.f.s. or g.p.m. and pressure

14 Ft. from Surface If nonflowing well give depth of standing water from surface. If flowing well describe control works. July 1.953. Date of completion of well..... Type of well rig. Keystone. # 50 -- (Howard an Son's Well Rig.) Date of commencement of well.....July..

LOG OF FORMATIONS

Water-bearing Formation, Casing Perforations, Edc.	Ohlef aquifer (water-bearing formation) 80 87	17	194 Ft. to 196 Ft.		

35 Ft. feet

	#
	30
rst	at
fi	Ď
 	ntered
<u>S</u>	Int
ğ	nool
36	
3	Φ

- interfingered with aquifer units Red Clay
- (open borehole?) from 67 to 205 ft. Well "screened"

1953

(Type and size of valve, etc.)

Water-bearing B	Perforat		Ohlef aquifer	forms	80		Other aquifers _10	104 704	Z						First water at	
	Type of material	Top Soil	Hard Kalitche	Light Clay	Hard Rock	White Clay	Hard Rock	Red Clay	Hard Kalitche	Red Clay	Hard Kalitche	Red Clay	Hard Rock	Red Clay		
	Thickness	10	m	ıν	1 0	N	N	2	7	15	17	75	, CU	5		
	To	10	13	19	23	28	30	8	87	102	119	167	196	502		
	From	0	2	13	18	23	58	ഉ	8	87	102	119	194	196		




Recap of Site Stratigraphic Setting

- Near Toe of Alluvial Fan Deposits (i.e., highly variable and complex)
- Up-slope of Playa Deposits, but within the Las Vegas Wash Aquitard (Leising, 2004)
- LV Wash "Aquitard" is leaky, and includes high-K units
- Steep hydraulic gradient from Piedmont toward Las Vegas Wash

Site Lithology








- brown) at about 30 ft show silts and clays Many boring logs (some reddish
- Caliche is common predictable depths but not at
- greater than 30 ft deep terminate in silt Not all borings or clay



Site "Hydro-Chemi-Stratigraphy"





- Water quality improves with depth
- Two of the eleven deeper samples < 500 mg/L TDS
- Producing
 aquifer TDS in
 this area is
 between 400 and
 800 mg/L

2



Preliminary Findings

- Continuous lithologic boundaries to vertical groundwater flow unlikely
- Deeper site groundwater (i.e., 60 to 65 ft) is in transition zone from poor-to-better quality groundwater
- Deeper site groundwater historically used for domestic and irrigation supply




Regional Hydrologic Setting

- Very low rainfall of 3 to 4 inches per year
- Recharge from Spring Mountain runoff on upper portion of alluvial fans
- Las Vegas Valley Main Well Field located north of the site
- Imported Lake Mead water recharged in 1990s near MWD
- Groundwater discharges to Las Vegas Wash
- LV Wash flows out of basin

Map of Groundwater Elevations in Deeper Aquifers






- Site is located near 2,000 ft contour line on the 1999 map
- GW elevations at the site ranged from 2,010 to 2,050 ft above msl, during Fourth Quarter 2012 monitoring event

5

Map of Potentiometric Surface Elevation **Changes 1990 to 1999**





- Water imported to the basin
- Injected near the Main Well Field
- Approximate 30-foot increase from 1991 to 1999 in Primary Producing Aquifers beneath the Rental Car Sites



Well Data for Deeper Well W043

ameco









Shallow Groundwater Hydrograph McCarran Airport Area - North





- Water levels at the site have increased by 3 to 4 ft from 1995 to 2012
- 2005 event is visible in the hydrograph






Site Characterization: Key Findings

- Narrow, straight plume
- Highest MTBE concentrations are 10 to 15 ft beneath the water table
- Heterogeneous mixture of silts, clays, sands, and gravels

Hypotheses for MTBE Fate & Transport Initial Phase Following Releases

ameco

Multi-Domain Transport and Storage




- Migration via sandier units
- Storage in siltier units



Hypotheses for MTBE Fate & Transport Later Phase, Following Source Removal




Multi-Domain Transport and Storage




- Residual mass mostly dissolved and within fine-grained units
- Back-diffusion from silts may continue for an extended time period
- Degradation to TBA...?

Unnecessary Following Characterization **Example Site: Remediation Determined**

ameco









- Source area cleanup and downgradient natural attenuation will be sufficient remedies.
- MTBE & TBA will not migrate past Maryland Parkway (>200 ug/L)
- MTBE & TBA will not migrate vertically to the primary producing aquifers (>200 ug/L)
- More...?

Next Steps

- Verify assumptions in current CSM (i.e., know and predict the extent of MTBE and TBA in groundwater)
- Determine needed degree of source remediation
- Other...?



Develop cross-sections and delineate three-dimensional **Potential Future Efforts**

Identify data gaps.

extent of MTBE and TBA.

- flow between shallow and deeper groundwater (including via Evaluate the hydraulic gradients and assess groundwater conduits).
- In the locations where elevated MTBE/TBA are detected, is the lithology high- or low-K?
- Optimize remedial efforts.
- Estimate hydraulic conductivities for finer-grained and coarser units.
- Is active cleanup of MTBE sequestered in low-K units needed?



References and Bibliography

- Broadbent & Associates, Inc., 2013, Lithologic Cross Section: Far Downgradient Investigation, Presentation to Nevada Department of Environmental Protection, February 5.
- Brothers, Kay and Katzer, Terry, 1988, Ground-water chemistry changes resulting from stressed aquifer systems in Las Vegas Valley, Clark County, Nevada. Las Vegas Valley Water District and the Nevada Division of Environmental Protection, Carson City, Nevada.
- Johnson, Michael, et al., (Southern Nevada Water Authority), 1998, Hydrogeology and Geology of the Las Vegas Valley, Clark County, Nevada, Field Trip Guide Book, December 16.
- Las Vegas Valley Groundwater Management Program website, 2013, water level data, http://www.lasvegasgmp.com/html/telemetry_index.html, April.
- Las Vegas Valley Water District, 1991, The Shallow Aquifer System in Las Vegas Valley, Nevada, August.
- Leising, Joseph F., 2004, Chemical Conditions in the Primary Producing Aquifers and Portions of the Shallow Groundwater System of the Las Vegas Valley in 2000. Southern Nevada Water Authority. March 7.
- Morgan, D.S., and Dettinger, M.D., 1996, Ground-water conditions in Las Vegas Valley, Clark County, Nevada; Part 2, Hydrogeology and simulation of ground-water flow: U.S. Geological Survey Water-Supply Paper 2320-B, 124 p.
- Pavelko, M.T., Wood, D.B., and Laczniak, R.J., 1999, Las Vegas, Nevada: *in* Galloway, D.L., Jones, D.R., and Ingeb-ritsen, S.E., eds., Land subsidence in the United States: U.S. Geological Survey Circular 1182, p. 49–64.
- Payne, Fred (Arcadis), 2011, California The Continuing Evolution of Groundwater Remediation Hydrogeology, Groundwater Resources Association Webcast, May 23.
- Plume, R.W., 1989, Ground-water conditions in Las Vegas Valley, Clark County, Nevada—Part I, Hydrogeologic framework: U.S. Geological Survey Water-Supply Paper 2320-A, 15 p.
- Wood, D.B., 2000, Water use and associated effects on ground-water levels, Las Vegas Valley and vicinity, Clark County, Nevada, 1980–95: Nevada Division of Water Resources, Water-Resources Information Report 35, 101 p.
- Zikmund, 1996, Extent and Potential Use of the Shallow Aquifer and Wash Flow in Las Vegas Valley, Nevada: Southern Nevada Water Authority



Preliminary Conceptual Site Model

Facilities Meeting Prepared for the February 4, 2014 Former Rental Car

CSM Efforts Since May 2013 Meeting



- Reviewed and integrated surficial geology
- Inclusion of new geologic and water quality data
- posted on section Review of completeness and accuracy of data
- Review of interpreted geology
- NDWR well databases and logs Evaluation of sediment trends vs. depth from
- Plotted concentration trends over time and over distance


Outline of Presentation



- Regional Geology
- Site Geology
- Hydrostratigraphy
- Regional Hydrology
- Regional Groundwater Flow and Gradients
- Results of Additional Analysis and Data Collection

Las Vegas Valley Basin







> 1,500 ft of unconsolidated sediments

- Alluvial fan deposits (coarser) interfingered with playa deposits (finer)
- Water table intersects surface at the Las Vegas Wash

Major Stratigraphic Units (Leising, 2004)








- No distinct lithologic boundaries
- Hydrostratigraphic definitions include:
- Age of sediments
- Water quality (TDS)
- Site located near transition from alluvial fan to playa deposits


Surficial Geology





Site Geology & Hydrostratigraphy (1 of 3)






- OGI (2009)
 interpreted finer unit
 starting at about 30ft
 bgs
- Note, "Clayey water bearing zone," is highly conductive

Site Geology & Hydrostratigraphy (2 of 3)








- Many boring logs show silts and clays (some reddish brown) at about 30 ft
- Caliche is common but not at predictable depths
- Not all borings greater than 30 ft deep terminate in silt or clay

Site Geology & Hydrostratigraphy (3 of 3)





- "Shallow" Geology upper 30 feet is predominantly coarser material (Silty Sand).
- "Deeper" Geology below 30 feet is predominantly fine grained with lenses of coarser material

OGI Slug Test Results (2009)



Table 6. Summary of Hydraulic Testing Results.

OMW-43c 25-30 Slug in		OMW-43b 45-50 Slug out	OMW-43b 45-50 Slug in	OMW-43a 55-60 Slug out	OMW-43a 55-60 Slug in	PMW-1c 25-30 Slug out	PMW-1c 25-30 Slug in	PMW-1b 45-50 Slug out	PMW-1b 45-50 Slug in	PMW-1a 55-60 Slug out	PMW-1a 55-60 Slug in	Screened Interval Well (ft bgs) Test Phase
No solution	Nandida	2.76E-03	2.93E-03	1.02E-03	9.58E-04	2.00E-04	2.34E-04	2.61E-04	2.54E-04	9.51E-05	1,11E-04	Hydraulic conductivity (cm/sec)
	No solution	7.83	8.30	2.90	2.71	0.57	0,66	0.74	0.72	0.27	0.31	Hydraulic conductivity (ft/d)
	Poor curve match	Excellent curve match	Excellent curve match	Excellent curve match	Excellent curve match	Good curve match	Fair curve match	Excellent curve match	Excellent curve match	Excellent curve match	Excellent curve match	Comments

Notes:
(1) The water level recovery rate for well OMW-43A was too rapid to allow sufficient data to be collected for a reliable estimate of hydraulic conductivity. Data indicate a very high conductivity.

Comparison of Slug Test Results




- K in the two clusters ranges from approximately 10⁻³ to 10⁻⁵ cm/s
- The highest K was measured in shallow wells in the offsite cluster well
- on-site and off-site cluster wells The lowest K was measured in the deepest screened wells, in both the
- The observed lithology corresponds to the slug test data:
- The deeper aquifer has fine grained clays and lower K values
- higher K values The shallower wells are set in fine-grained sand and silty sand and have
- Upper HSU: range of hydraulic conductivity (K) estimates is higher.
- Lower HSU: range of K estimates is lower.

Analysis of Deeper Geologic Site Data



- Nine drillers logs with sufficient detail for
- Observations:
- increased frequency of fine grained sediments below 30 ft bgs
- No laterally continuous clay units




Regional Hydrologic Setting



- Very low rainfall of 3 to 4 inches per year
- Recharge from Spring Mountain runoff on upper portion of alluvial fans
- Las Vegas Valley Main Well Field located north of the site
- Imported Lake Mead water recharged in 1990s near MWD
- Groundwater discharges to Las Vegas Wash
- LV Wash flows out of basin

Map of Potentiometric Surface Elevation Changes 1990 to 1999







- Water imported to the basin
- Injected near the Main Well Field
- Approximate 30-foot increase from 1991 to 1999 in Primary Producing Aquifers beneath the Rental Car Sites

Well Data for Deeper Well W043








Shallow Groundwater Hydrograph McCarran Airport Area - North






- North of the site water level increased about 10 ft from 1991 through 1995
- the site have increased by 3 to 4 ft from 1995 to 2012
- 2005 event is visible in the hydrograph

Groundwater Gradient






- Depth to water table decreases
- Steepened water table downgradient downgradient of source areas

Site "Hydro-Chemi-Stratigraphy"





- Water quality improves with depth
- Two of the eleven deeper samples < 500 mg/L TDS
- Producing
 aquifer TDS in
 this area is
 between 400 and
 800 mg/L


Summary of Findings



- Continuous lithologic boundaries to vertical groundwater flow unlikely
- poor-to-better quality groundwater Deeper site groundwater (i.e., 60 to 65 ft) is in transition zone from
- Deeper site groundwater historically used for domestic and irrigation

Conceptual Site Model





Potential Mechanisms For Vertical Distribution of MTBE



- Vertical Flow
- Conduits
- Historically lower water table

Normal Faults Perpendicular to GW Flow

NGWA, 1948







Figure 1-7. -- Generalized Geologic Cross Section of the Las Vegas Valley.

Projection of Regional Fault Traces





Las Vegas Valley Basin






Figure 54. Schematic Cross-Section of the Shallow Groundwater System in Pre-Development Times.

Pre-development groundwater input to the near surface occurred (1) along faults and (2) from the Las Vegas Springs Aquifer (Unit B) through the Las Vegas Wash Aquitard (Unit A). Arrows indicate flow direction and approximate relative magnitudes. Hatchures indicate saturation. The Duck Creek Aquifer (Unit C) may also have received water from the Las Vegas Springs Aquifer.





Figure 55. Schematic Cross-Section of the Present Shallow Groundwater System.

The present shallow system originates from (3) surface application and (2) continued slow upward migration of groundwater through the Las Vegas Wash Aquitard in the eastern portion of the Valley. Note that upward movement along the fault at (1) has ceased due to reduced heads in the Las Vegas Springs Aquifer, and that shallow groundwater may not be continuous from place to place.

- Historically shallow groundwater was fed by
- upward flow along faults,
- upward vertical flow,
- surface water recharge
- By 1990
- Over pumping in deeper aquifers had reduced upward flow along faults
- Surface application of water is more significant
- By 1999 artificial recharge had helped water levels recover
- Has flow along faults resumed?
- Has upward vertical flow increased?

Groundwater Gradient Profile






- Steepened water table downgradient of source areas
- Impediment to horizontal flow?
- Upward flow below source areas?

Shallow Groundwater Hydrograph McCarran Airport Area - North






- North of the site water level increased about 10 ft from 1991 through 1995
- the site have increased by 3 to 4 ft from 1995 to 2012
- 2005 event is visible in the hydrograph

Groundwater Levels in Multi-Depth Wells








Concentration Trends with Distance and Time


Upper HSU: Palo Verde to Wilbur






Upper HSU: Swenson to Maryland





Upper HSU: MTBE Arrival Times and Concentration-Distance Curve






Lower HSU: MTBE Trends



- TBA is detected
- Rate of migration appears slower

Project Lifecycle Schedule Forecast







End of Presentation

APPENDIX C

GROUNDWATER ELEVATION CONTOURS AND PLOTTED MTBE AND TBA CONCENTRATIONS IN MONITORING WELLS

