PROPOSED REGULATION OF THE STATE ENVIRONMENTAL COMMISSION

P2009-05

EXPLANATION – This petition amends LCB File No. R190-08, which became effective on April 23, 2009, but has not been codified as of October 1, 2009. Matter in *blue italics* is from R190-09; matter in *green italics* is new; matter in brackets [omitted material] is material to be omitted.

AUTHORITY: §§1-7, NRS 445B.210.

Section 1. Chapter 445B of NAC is hereby amended to read as follows:

LCB File No. R190-08, eff 4/23/09. Sec. 4. 1. The sources listed below must install, operate and maintain the following control measures which constitute BART and must not emit or cause to be emitted NO_x , SO_2 , or PM_{10} in excess of the following limits:

(a) For power-generating units numbers 1 and 2 of NV Energy's Fort Churchill Generating Station, located in hydrographic area 108:

	NO _x		SO_2		PM_{10}	
UNIT (Boiler)	Emission Limit (lb/10 ⁶ Btu, 12- month rolling average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 24-hr average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 3-hr average)	Control Type
1	0.20	Low NO _x	0.05	Pipeline	0.03	Pipeline
2	0.16	burners with flue gas recirculation	0.05	and/or No. 2 fuel oil	0.03	natural gas and/or No. 2 fuel oil

(b) For power-generating units numbers 1, 2 and 3 of NV Energy's Tracy Generating Station, located in hydrographic area 83:

	NO_x		SO_2		PM_{10}	
UNIT (Boiler)	Emission Limit (lb/10 ⁶ Btu, 12- month rolling average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 24-hr average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 3-hr average)	Control Type
1	0.15	Low NO _x burners with	0.05		0.03	
2	0.12	flue gas	0.05	Pipeline natural gas	0.03	Pipeline natural gas
3	0.19	Low NO _x burners with selective non- catalytic reduction	0.05	and/or No. 2 fuel oil	0.03	and/or No. 2 fuel oil

(c) For power-generating units numbers 1, 2 and 3 of NV Energy's Reid Gardner Generating Station, located in hydrographic area 218:

	NO_x		SO_2		PM_{I0}	
UNIT (Boiler)	Emission Limit (lb/10 ⁶ Btu, 12- month rolling average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 24- hr average)	Control Type	Emission Limit (lb/10 ⁶ Btu, 3-hr average)	Control Type
1	0.20	Rotating	[0.25] 0.15	Wet soda ash	0.015	
2	0.20	Opposed Fire	[0.25] 0.15	flue gas	0.015	Fabric filter
3	0.28	Air with Rotamix ¹	[0.25] 0.15	desulfurization	0.015	

¹ Rotamix is a technology for adding selective non-catalytic reduction using ammonia or urea-based reagent.

(d) For power-generating units numbers 1 and 2 of Southern California Edison's Mohave Generating Station, located in hydrographic area 213:

	NO_x			SO_2		PM_{10}	
	Emission Limit	Mass		Emission Limit		Emission	
	(lb/10 ⁶ Btu, 12-	Emission		$(lb/10^6 Btu, 30-$		Limit (lb/10 ⁶	Control
UNIT	month rolling	Rate (lb/hr,	Control Type	day rolling	Control Type	Btu, 3-hr	Type
(Boiler)	average)	1-hr average)		average)		average)	
1	0.15	788	Low NO _x burners with over-fire air	0.0019	Conversion to	0.0077	Conversion
2	0.15	788	and conversion to pipeline natural gas only	0.0019	pipeline natural gas only	0.0077	to pipeline natural gas only

- 2. The control measures established in subsection 1 may be replaced or supplemented with alternative technologies approved in advance by the Director, provided that the emission limits in subsection 1 are met. The established or approved control measures must be installed and operating:
 - (a) For NV Energy's Fort Churchill, Tracy and Reid Gardner generating stations:
 - (1) On or before January 1, 2015; or
- (2) Not later than 5 years after approval of Nevada's state implementation plan for regional haze by the United States Environmental Protection Agency Region 9,

 → whichever occurs first.
- (b) For Southern California Edison's Mohave Generating Station, at the time that each unit resumes operation.

- 3. If the ownership of any BART regulated emission unit changes, the new owner must comply with the requirements set forth in subsection 2.
- 4. For purposes of this section, emissions of PM10 include the components of PM2.5 as a subset.