## **PROPOSED REGULATION OF**

## THE STATE ENVIRONMENTAL COMMISSION

## LCB File No. R118-14

## With Proposed Agency Amendments

November 14, 2014

EXPLANATION – Matter in *italics* is new; matter in brackets [omitted material] is material to be omitted. Matter in <u>bold double</u> <u>underline</u> is a proposed Agency Amendment subsequent to LCB review; matter in double strikethrough brackets [omitted material] is material to be omitted.

Sec. 8. NAC 445A.66085 is hereby amended to read as follows:

445A.66085 "Lead-free" means, with regard to:

1. Solder and flux, that not more than 0.2 percent of the composition of the solder or flux

is lead.

2. Pipes, [and] fittings [] and fixtures, that not more than [8] a weighted average of 0.25

percent of the composition of the *wetted surfaces of the* pipe, [or] fitting or *fixture* is lead [.],

as calculated in accordance with Standard 372 of the American National Standards Institute

and the National Sanitation Foundation International, as adopted by reference in NAC

445A.6663.

3. Gate valves which are 2 inches in diameter or more, service saddles and fire hydrants, that:

(a) Not more than 8 percent of the composition of the gate valve, service saddle or fire hydrant is lead; and

(b) The gate valve, service saddle or fire hydrant complies with Standard 61 of the <u>American National Standards Institute and the National Sanitation Foundation</u> International, as adopted by reference in NAC 445A.6663. Sec. 12. NAC 445A.67125 is hereby amended to read as follows:

445A.67125 1...

2. The choice of materials for [the pipes of] a distribution system must be based on the properties of the soil and water. In areas where:

(a) The water is corrosive, [metallic pipe] [metallic pipe] must not be used.

(b) The groundwater or soil is contaminated with volatile or synthetic organic chemicals, plastic [pipe] and [gasketed pipe] gaskets must not be used.

<u>unless otherwise approved by the Division or the appropriate district board of health in</u> <u>accordance with NAC 445A.6665</u>.

3. Any pipes, fittings, *fixtures*, solder, [or] flux, *service saddles, fire hydrants and gate valves* used in the installation or repair of a public water system must be lead-free. [and comply with section 316.1.3 of the Uniform Plumbing Code.]